

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE	3. REPORT TYPE AND DATES COVERED FINAL	
4. TITLE AND SUBTITLE FY92-93 HBCU/MI Instrumentation for the Pulsed Power and Plasma Sciences Laboratory at the University of New Mexico			5. FUNDING NUMBERS XXXXXX 4276/AS 62228D	
6. AUTHOR(S) Professor Schamiloglu				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of New Mexico Albuquerque, NM 87131-1356			8. PERFORMING ORGANIZATION REPORT NUMBER AFOSR-TR- 95 0165	
9. SPONSORING MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/NE 110 Duncan Avenue Suite B115 Bolling AFB DC 20332-0001			10. SPONSORING MONITORING AGENCY REPORT NUMBER F49620-93-1-0585	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION AVAILABILITY STATEMENT APPROVED FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED			12b. DISTRIBUTION CODE	
13. ABSTRACT SEE FINAL REPORT ABSTRACT				
14. SUBJECT TERMS			15. NUMBER OF PAGES	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UNCLASSIFIED	

DTIC
ELECTE
MAR 27 1995



The University of New Mexico

Department of Electrical and
Computer Engineering
Room 110, EECE Building
Albuquerque, NM 87131-1356
(505) 277-2436

ORIGINAL

**Final Technical Report Submitted to AFOSR:
FY92-93 HBCU/MI Instrumentation for the
Pulsed Power and Plasma Sciences Laboratory
at the University of New Mexico
(Grant AFOSR #F49620-93-1-0585)**

30 November 1994

Edl Schamiloglu, Associate Professor, Principal Investigator
Charles Fleddermann, John Gahl, & Donald Shiffler, CO-PIs
Pulsed Power & Plasma Science Laboratory

Department of Electrical and Computer Engineering
University of New Mexico
Albuquerque, NM 87131

Accession For	
NTIS CR&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution	
Date	
DTIC	Unannounced
A-1	

19950322 162

Table of Contents

Section I. Executive Summary	3
Section II. List of Acquired Equipment	4
Section III. Description of Research Program	7
Section IV. References	13
Appendix A. Memorandum requesting changes in original proposed acquisitions	14
Appendix B. Published journal papers where equipment was used	22

I. Executive Summary

The Pulsed Power & Plasma Science Laboratory at the University of New Mexico (UNM) is pleased to have equipped its laboratory with modern instrumentation in support of its AFOSR-funded program on high power microwave sources. The instrumentation acquired can be broken broadly into three categories:

1. Microwave measurement/calibration (network analyzer and components)
2. Data acquisition (digital oscilloscopes, computers, LabView)
3. High vacuum capabilities (turbo pumps, residual gas analyzer).

This report describes the instrumentation and how it is used in support of the research program.

II. List of Acquired Equipment

The next two pages provides a comprehensive list of equipment that was purchased on this grant, and highlights minor deviations from the AFOSR-approved modified list of equipment (included as Appendix A to this report).

Network Scalar Analyzer			
HP 8757XC	20 GHz Coaxial Synthesized	\$36,225.00	
W/ Opt. 52B	Scalar System		
Opt 002	Internal Power Cal	\$2,250.00	
Opt 001	Fourth Detector Input	\$1,440.00	
			\$39,915.00
HP 85037B	Precision Detector	\$1,665.00	
HP 85025E	AC/DC Detector	\$1,080.00	
HP 11679B	Detector Cable 200 ft	\$337.50	
HP 85025E	AC/DC Detector	\$1,080.00	
HP 85027E	Directional Bridge	\$2,853.00	
HP 11679A	3 Detector Cables 25 ft	\$337.50	
			\$7,353.00
HP 85023B	Verification Kit for SMA	\$900.00	
HP 85023C	Verification Kit for Type-N	\$630.00	
HP 11636B	Power Divider	\$945.00	
HP 11667B	Power Splitter	\$963.00	
			\$3,438.00
			\$50,706.00
Oscilloscopes			
TDS 320	3 Digital Oscilloscope	\$8,456.00	
	2 Ch, 500 Ms/s with GPIB bus		
TDS 350	2 Digital Oscilloscope	\$7,184.00	
	2 Ch, 1Gs/s with GPIB bus		
	Thermal Printer for Scope	\$180.56	
TDS 644A	3 Color Digital Oscilloscope	\$45,145.80	
	4 Ch, 2 Gs/s		
			\$60,966.36
Computers and DAQ			
	Mac IIcx with 20 Meg RAM		
	and 300 MB Hard Drive	\$2,987.98	
	Optical Drive	\$964.40	
	HP 550C Deskwriter Printer	\$539.97	
	LabView 3.0 for Mac	\$1,296.75	
	NB-GPIB Board w/cable	\$539.38	
	Thick Net Adapter	\$70.38	
	Digital I/O Board	\$319.50	
	Connecting Block and Cables	\$216.00	
			\$6,934.36
	486DX2 System With 540MB	\$6,370.00	
	Hard Drive, 16MB RAM		
	21" SVGA Monitor		
	Optical Drive, Tape Backup		
	Optical discs (10)	\$329.80	
	LabView3.0 for Windows	\$1,296.75	
	GPIB Board	\$539.37	
	Digital I/O Board	\$355.50	
	Connecting Block	\$138.79	
	HP 550C Deskjet Printer	\$546.44	
			\$9,576.65
			\$16,511.01
Turbo Pumps			
	Turbo Pump	\$11,175.26	
	Controller for Turbo Pump	\$5,780.00	
			\$16,955.26
Gas Analyzer			
	Residual Gas Analyzer	\$7,500.00	
	Analyzer Head	\$1,570.00	
			\$9,070.00
Total			\$154,208.63

Differences:

- 6 -

Oscilloscopes: TDS 544A did not meet our requirements
therefore, we ordered three TDS 644A's.

Computers and DAQ:

Did not get DAQ software - used other funds
to buy Quatro Pro and Paradox Software

Used other funds to buy Ethernet cards (\$150)

Upgraded to 21" Monitor for 486 system

III. Description of Research Program

The present AFOSR-funded grant on high power microwave sources has three research components:

1. High efficiency vacuum backward-wave oscillators
2. Long pulse vacuum and plasma-filled backward-wave oscillators
3. Ferroelectric cathodes for high power microwave sources.

The microwave measurement/calibration equipment is used on the two backward-wave oscillator (BWO) experiments, the data acquisition is used on all three components of the research program, and the high vacuum equipment is used on the long pulse BWO and on the ferroelectric cathode experiments.

In order to better describe the instrumentation, it would be useful to display photographs of the three experiments, and photographs of some of the acquired equipment.

Sinus-6 experiments

The study of high efficiency vacuum BWOs is performed on the Sinus-6 experiment (Fig. 1). This experiment uses LabView 3.0 to acquire and process the data that is taken with the digital oscilloscopes. In addition, the network analyzer is used to calibrate all of the microwave diagnostics and is used as a local oscillator to mix with the generated microwaves in a heterodyne scheme to measure frequency (Figs. 2-3).

These instruments were used to acquire and analyze the data that was used in a recent publication by our group.¹ It is essential to state that the data and understanding presented in this paper would not have been possible without the updated equipment.

Long pulse BWO experiments

The study of long pulse vacuum and plasma-filled backward-wave oscillators is performed using a modified PI-110A electron beam accelerator (Fig. 4, top).

This experiment utilizes the data acquisition instrumentation. In addition, it will use the turbo pump and the gas analyzer when it operates at higher power levels than the present time.




FIG. 1. Photograph of Sinus-6 repetitively-pulsed electron beam accelerator (top) and output of BWO microwave source (bottom).




FIG. 2. Array of four digital oscilloscopes (top) and network analyzer (bottom).



FIG. 3. Photograph of screen room showing the computer, digital oscilloscopes, and network analyzer (top). Doctoral candidate Larald Moreland analyzing a shot using LabView (bottom).





FIG. 4. Photograph of long pulse BWO (top) and ferroelectric cathode test stand (bottom).

Ferroelectric cathode devevelopment

This experiment utilizes the high vacuum equipment as well as the data acquisition equipment. The ferroelectric cathode test stand is shown in Fig. 4, bottom. The results published in a recent paper² used the data acquisition equipment. The residual gas analyzer will be of particular use to this experiment since it will look for evidence of neutrals and plasmas emanating from the cathode periphery. It is important to document whether the ferroelectric electron emission mechanism is accompanied by plasma-based effects.

IV. References

1. L. D. Moreland, E. Schamiloglu, R. W. Lemke, S. D. Korovin, V. V. Rostov, A. M. Roitman, K. J. Hendricks, and T. A. Spencer, "Efficiency Enhancement of High Power Vacuum BWO's Using Nonuniform Slow Wave Structures," IEEE Trans. Plasma Sci. **22**, 554 (1994).
2. T. C. Cavazos, W. L. Wilbanks, C. B. Fleddermann, and D. A. Shiffler, "Repeatable electron emission from (Pb,La)(Zr,Ti)O₃ ferroelectric cathodes using direct-current reset," Appl. Phys. Lett. **65**, 2612 (1994).